
DURATION® SHAKE PANELS





General Specs:

Material: Solid Poly Ash Width: 47-7/8"

Description: Even Butt Simulated Shakes Overlap: 1-1/4"

Surface: Sanded Smooth Overlap Thickness: 7/8" on 5/8", 3/4" on 7/16"

Finish: None – Ready for Finish Paint Pattern Types: A & B

Thickness: 7/16" or 5/8" Butt to 3/16" Top Note: All measurements +/- 1/16"

Variable Specs:	Height:	Reveal:	Coverage:	Bundle Size:	Bundles/Sq	Pieces/Sq
7/16 x 8	7-1/4"	6"	2.0 SF/Panel	8 Pieces	6.33	50
5/8 x 8	7-1/4"	6"	2.0 SF/Panel	8 Pieces	6.33	50
5/8 x 10	9-1/4"	8"	2.66 SF/Panel	6 Pieces	6.33	38

Major Benefits over Individual Wood Shakes:

- As much as 6-10 times less labor (faster install)
- No clearance requirements (e.g. adjacent to roofing material on dormers)
- Very heavy (up to 5/8") butt for great shadow lines
- Impervious to water won't rot, decay, or be affected by insects
- Can cut a dormer side on the ground and then install the pieces
- Paint ANY color
- Paint will last longer since product is stable and does not cycle moisture
- Requires no back or edge sealing
- Minimal waste
- Environmentally friendly (70% recycled content)
- No cracking, splitting, or tannin bleed

Major Benefits over PVC or Vinyl Systems:

- Stable no gapping or room for expansion and contraction required
- Ability to adjust course heights as needed
- Much more substantial and "real" appearance
- Feel to the touch is authentic
- More environmentally friendly (70% recycled content)
- Unaffected by high heat (reflection of Low E coated windows, etc.)
- Can be painted any color and color can be changed in the future
- Easier to repair or paint in future